

Parts	Rule
Handlebars (including mounts and pads), grips and hand controls	Free
Throttle	Free
Frame and Sub-frame	OEM. May be strengthened by way of gussets but must retain original design.
Triple Clamps	OEM
Front Forks	Free but must retain OEM fork tubes and sliders
Rear Suspension	Free but must retain OEM outer casing and shaft, including shock tube and gas cylinder.
Wheels	
Hubs and spokes	OEM
Rims, rim locks, spacers, tyres, and tubes	Free but the diameter of the wheel must be the same as the homologated machine For ATVs, the width of the wheel base must remain within +/- 10% of the homologated machine.
Axles	OEM
Braking System	
Brake linings	Free
Cables and hydraulic lines	OEM
All other parts	OEM
Swing Arm (2 wheelers)	OEM
ATV a-arms and Swing Arms	OEM, but may be modified to alter ride height/width.
Foot pegs & Foot Controls	Free
Motor	
Bearings & seals	Free
Base gasket	Free
Piston & Ring	OEM. If the OEM piston has two or more rings, then two or more rings must be fitted
All other parts	OEM. <u>Additional Notes:</u> For avoidance of doubt: <ul style="list-style-type: none"> • No material may be added to, or removed from, the compression or combustion chambers, inlets and/or exhaust tracts. This includes the removal of machine markings and casting dags etc. • The alteration of cams, camshafts, cylinder porting and rotary valves is prohibited.
Intake System including Carburettor	
Jets & needle (but not slide)	Free
Reeds & Reed block	OEM.
All other parts	OEM
Electrical System	
Spark plug	Free
Kill switch (2 wheelers)	Free, but a working kill switch must be fitted
Tether switch (ATV)	Free, but must have wrist cord
CDI	OEM
All other parts	OEM
Exhaust System	OEM
Seals, O rings, exhaust packing	Free
All other parts	OEM
Seat	Free
Plastics	Free
Air Box	OEM but may be drilled before the filter
Air Filter	Free
Clutch	
Clutch basket/drum	OEM
Friction and drive disks (manual clutch)	Free

CVT weights and clutch springs (ATV only)	Free
Clutch shoes (auto clutch)	OEM
Clutch springs, spring washers and shims	OEM
Clutch springs (manual clutch)	OEM
Cables and hydraulic lines	OEM
All other parts	OEM
Gearbox and Drive System	
External gearing	Free
Chain	Free
All other parts	OEM
All Bearings, Seals and O rings	Free
All Screws, Bolts & Other Fastening	Free
All Fluids and Oils	Free
Graphics and Paint Work	Free
Lubrication System	If homologated machine is oil injected (auto lube), the system must be used.
Fuel and Oil Caps (includes fuel cap breather hose)	Free, but must prevent spillage
Fuel lines	Free but must be the same internal diameter as OEM and made of material suitable for carrying fuel.
Oil filters	Free
Optional Additional Parts	
Holeshot Kits/clips	Not permitted
Steering dampeners	Not permitted
Engine hour meter	Free