

- 0 The rules for this class will apply to all Road Race Championship and endurance Championship races. At other meetings these rules will apply unless varied in the Supplementary Regulations, but not contradicting the class rules.
- 0.1 This class of motorcycle requires a production motorcycle available and on sale to the mass public in New Zealand. It is the competitor's responsibility to make sure that the machine's engine configuration is the same as the manufacturer's specification. All parts unless mentioned elsewhere *MAY NOT* be interchanged between models, generations, and year of manufacture (*YOM*). Bike components are as per the VIN plate for that bike (*see rule 1b*).
- 0.2 Pro Twin motorcycles require an MNZ homologation. At least 10 production machines of that make and model must have been imported into New Zealand, by the manufacturer or the New Zealand distributor representing the manufacturer.
- 0.3 Where a New Zealand Importer (distributor) does not exist and the Importer (distributor) is based in Australia and communication re homologation is not forthcoming then with MNZ Road Race Commissioner approval a New Zealand retail outlet could be engaged to provide suitable homologation.
- 0.4 All items not mentioned in the following articles must remain as originally produced by the manufacturers, remain fitted and operational for that model.

0.5 The frame number of the machine will be registered by the competitor to the Technical Department. This must be the machine that is ridden in all races during the event.

1. MACHINE SPECIFICATIONS:

- a) Two cylinder four strokes up to 690cc standard engines.
- b) Be fitted with VIN compliance plates for that model of machine. The only exception to this is if the machine has been supplied direct from the manufacturer and was not intended for use on public roads. However, the onus is on the competitor to ensure the machine is indeed identical to the machine available for sale to the mass public of New Zealand.
- c) Be of a make and model lawfully imported and sold to the mass public in New Zealand.
- d) Be as constructed by the original manufacturer.
- e) Machines with re-bored cylinders must remain within that model's OEM capacity limits (*i.e. second oversize, 0.5mm*).

2. NUMBERS:

- a) Number plate colours, size and placement: (*Refer to the Technical Appendix*)

3. FUEL:

- a) refer to the Technical Appendix

4. TYRES:

- a) Be commercially available from within New Zealand.
- b) Be not less than the machine manufacturer's recommended speed rating.
- c) Be worn no more than to the minimum tread depth indicators.
- d) Can be manufactured for road use (IE BE DOT approved) or for competition use.
- e) Not have an augmented or modified tread pattern.
- f) For all events other than endurance races only one set of tyres per meeting will be permitted for races where points for MNZ championships are awarded.
- g) Front and rear tyres fitted must conform to the relevant tyre manufacturers' specifications regarding rim width.
- h) When a race or practice session has been declared 'wet', the use of a wet tyre is allowed.
- i) Any number of wet tyres may be used should the meeting be declared 'wet'.

5. THE FOLLOWING MAY BE REMOVED:

- a) Air injection pollution control system.
- b) Carburettor anti-icing device.

THE FOLLOWING MAY BE FITTED:

- a) Ride height adjuster, providing no alterations are required to either frame or swing arm.

- b) Accessory fairing, front guard and bodywork may be fitted.
- c) Quick shifting devices.

6. THE FOLLOWING MAY BE REPLACED WITH PARTS NOT MANUFACTURED BY THE MANUFACTURER OF THE MACHINE:

- a) Fairing, screen, rear seat unit/bodywork (to provide for the mounting of a rear number board), rider's seat, mudguards and tank covers.
- b) Handlebar mounted levers, and controls including the front brake master cylinder.
- c) External gearing and chain but not chain pitch.
- d) Exhaust system.
- e) A fuel tuning device (i.e. Power Commander) or ECU flashing device is permitted. Except for the fitting of the associated wires for such a device, the wiring loom must remain standard and intact.
- f) Rear suspension damping units and springs. The link arms (dog bones) may be changed or modified but the suspension linkage must remain standard. Original attachments to the frame must be used.
- g) Battery, but the replacement must be capable of starting the machine prior to, and post-race.
- h) The base and head gaskets may be replaced with aftermarket equivalents; however, OEM thickness MUST be retained.
- i) The fitment of an aftermarket sub-frame or modification to the existing OEM sub-frame is allowed providing that the construction is comparable to the original OEM parts (i.e. strength and design). Items such as the battery, wiring, ecu, etc, must be fitted to the aftermarket sub-frame in the same position as the original OEL fitment. The aforementioned items must be secure and not able to be dislodged from the sub-frame in the event of a crash. Where a make of machine has no sub-frame or the sub-frame is permanent (can't be removed), then other than alterations for the fitting of a tail piece, and the mounting of brackets for seat and tail unit, no alterations allowed.
- j) Wheel spacers.

7. THE FOLLOWING IS PROHIBITED:

- a) The fitment of aftermarket traction control units is not permitted.
- b) Lifting of the fuel tank is not permitted.

Below are the Balancing Rules applicable as of November 1st 2025 for the Appendix E:

Pro Twin eligible machines, componentry and balancing rules as of 1/9/2025

These rules are to be read in conjunction with Appendix E.

Appendix E capacity and homologation requirements do not convey entry to the class:

1. The make, model year of the machine must be noted below for it to be eligible
2. The current balancing rules must be applied to the time of competition.
3. Unless specified in Appendix E, or below no other modifications are allowed.
4. Specific to each model specified and can be amended with Road Race Commissioner Approval at any time through the year to ensure continued parity of machinery within the class.

Eligible Machines and Performance balancing modifications allowed.

Suzuki SV650 all years

The following items may be used or changed as outlined.

- a) Engine cam wheels may be slotted to alter valve timing.
- b) Conrod bolts or complete conrods can be changed with after-market items.
- c) FRONT FORKS: Externally the front forks must remain standard (as per the VIN and the bikes homologation). Top caps and external damping adjusters must be completely standard. Dust seal wipers must remain fitted. Replacement inner tubes must have the same surface coating type and colour as standard. Spring spacers and washers may be changed from the OEM items. Springs, free to change. Emulators or any proprietary Emulator type devices for use with the original damper rods may be fitted. Damper Compression Holes may be drilled over size. Replacement with aftermarket cartridges is prohibited. Spring spacers and washers may be changed.

7. Yamaha MT07 655cc model years 2014 - 2024

The following items may be used or changed as outlined.

- a) Engine cam wheels may be slotted to alter valve timing.

- b) Can derestrict the rubber manifolds (Yamaha Part #1WS-13635-00) between the throttle body and the cylinder head. As an alternative the genuine part from the Yamaha 690cc HO R7 can be fitted.**
- c) Airbox is free to change or remove**
- d) Air intake funnels are free to remove or modify**
- e) Air filter is free to change or remove
- f) Throttle bodies must remain as standard. Assisted air induction or ram air systems and devices are not allowed.
- g) FRONT FORKS: Externally the front forks must remain standard (as per the VIN and the bikes homologation). Top caps and external damping adjusters must be completely standard. Dust seal wipers must remain fitted. Replacement inner tubes must have the same surface coating type and colour as standard. Spring spacers and washers may be changed from the OEM items. Springs, free to change. Emulators or any proprietary Emulator type devices for use with the **original** damper rods may be fitted. Damper Compression Holes may be drilled over size. Replacement with aftermarket cartridges is prohibited. Spring spacers and washers may be changed.

8. **Yamaha MT07 689cc (HO) model years 2014 - 2024**

The following items may be used or changed as outlined.

- a) FRONT FORKS: Externally the front forks must remain standard (as per the VIN and the bikes homologation). Top caps and external damping adjusters must be completely standard. Dust seal wipers must remain fitted.
- b) Replacement inner tubes must have the same surface coating type and colour as standard. Spring spacers and washers may be changed from the OEM items. Springs, free to change. Emulators or any proprietary Emulator type devices for use with the **original** damper rods may be fitted. Damper Compression Holes may be drilled over size. Replacement with aftermarket cartridges is prohibited. Spring spacers and washers may be changed

9. **Yamaha R7 655cc all years**

The following items may be used or changed as outlined.

- a) Engine cam wheels may be slotted to alter valve timing.
- b) Can derestrict the rubber manifolds (Yamaha Part #1WS-13635-00) between the throttle body and the cylinder head. As an alternative the genuine part from the Yamaha 690cc HO R7 can be fitted.**
- c) Airbox is free to change or remove**
- d) Air intake funnels are free to remove or modify**
- e) Air filter is free to change or remove**
- f) Throttle bodies must remain as standard. Assisted air induction or ram air systems and devices are not allowed.
- g) FRONT FORKS: The following are free to change:
 - i. Oil type and viscosity
 - ii. Oil levels/air gap
 - iii. Spring rates
 - iv. Spring preload spacers or washers
 - v. Fork cartridge bottoming cones and the corresponding bottoming cups may be freely modified and or removed from the cartridge rods.
- h) ALL other front suspension parts must remain standard.

10. **Yamaha R7 689cc (HO) all years**

The following items may be used or changed as outlined.

- a) FRONT FORKS: The following are free to change:
 - i. Oil type and viscosity
 - ii. Oil levels/air gap
 - iii. Spring rates
 - iv. Spring preload spacers or washers
 - v. Fork cartridge bottoming cones and the corresponding bottoming cups may be freely modified and or removed from the cartridge rods.
- b) ALL other front suspension parts must remain standard.

11. Kawasaki ER6 all years

The following items may be used or changed as outlined.

- a) Engine cam wheels may be slotted to alter valve timing.
- b) Conrod bolts or complete conrods can be changed with after-market items
- c) FRONT FORKS Externally the front forks must remain standard (as per the VIN and the bikes homologation). Top caps and external damping adjusters must be completely standard. Dust seal wipers must remain fitted. Replacement inner tubes must have the same surface coating type and colour as standard. Spring spacers and washers may be changed from the OEM items. Springs, free to change. Emulators or any proprietary Emulator type devices for use with the **original** damper rods may be fitted. Damper Compression Holes may be drilled over size. Replacement with aftermarket cartridges is prohibited. Spring spacers and washers may be changed.

12. Kawasaki 650 Ninja all years

The following items may be used or changed as outlined.

- a) Engine cam wheels may be slotted to alter valve timing.
- b) Conrod bolts or complete conrods can be changed with after-market items
- c) FRONT FORKS: Externally the front forks must remain standard (as per the VIN and the bikes homologation). Top caps and external damping adjusters must be completely standard. Dust seal wipers must remain fitted. Replacement inner tubes must have the same surface coating type and colour as standard. Spring spacers and washers may be changed from the OEM items. Springs, free to change. Emulators or any proprietary Emulator type devices for use with the **original** damper rods may be fitted. Damper Compression Holes may be drilled over size. Replacement with aftermarket cartridges is prohibited. Spring spacers and washers may be changed.

13. Hyosung 650 all years

The following items may be used or changed as outlined.

- a) Engine cam wheels may be slotted to alter valve timing.
- b) Conrod bolts or complete conrods can be changed with after-market items
- c) FRONT FORKS Externally the front forks must remain standard (as per the VIN and the bikes homologation). Top caps and external damping adjusters must be completely standard. Dust seal wipers must remain fitted. Replacement inner tubes must have the same surface coating type and colour as standard. Spring spacers and washers may be changed from the OEM items. Springs, free to change. Emulators or any proprietary Emulator type devices for use with the **original** damper rods may be fitted. Damper Compression Holes may be drilled over size. Replacement with aftermarket cartridges is prohibited. Spring spacers and washers may be changed.